



RUS26126-KS

直线循环滚柱轴承组件

舍弗勒ID：
0013677650004

带间隔元件的直线滚珠轴承，带断面润滑街头 RUS

技术信息

主要尺寸和性能数据

L_{tot}	138.1 mm	total length
B	40 mm	Width
H	26 mm	Height
C	122,000 N	Basic dynamic load rating
C_0	103,000 N	Basic static load rating
$\approx m$	0.81 kg	重量

安装尺寸

L_1	93 mm	Mounting dimension
J_B	30 mm	Mounting dimension
J_L	68 mm	
H_1	0.2 mm	
L_4	103 mm	minimum support length
L_W	14 mm	
H_4	21 mm	
T_5	10.2 mm	
G_1	M6	fixing screws top (DIN ISO 4762-12.9)
$G_1 M_A$	17 Nm	Tightening torque fixing screws
K_3	M4	fixing screws below (DIN ISO 4762-12.9)
$K_3 M_{Amax}$	5 Nm	Tightening torque fixing screws
D_2	4.9 mm	
L_S	132.1 mm	
A_4	13.2 mm	
	M6	Lubrication connection DIN3405-A
	6 mm	

Related products

VUS26126-A	Adjustment gib
UG9741, UGN9741-A,	suitable Guide rail
UZ9741, UZN9741-A,	
U FK4710, UFB6412	

