



## RUS26086

### 直线循环滚柱轴承组件

舍弗勒ID：  
0013734040004

带间隔元件的直线滚珠轴承 RUS

## 技术信息

### 主要尺寸和性能数据

$L_{tot}$	90 mm	total length
L	86.4 mm	
B	40 mm	Width
H	26 mm	Height
C	76,000 N	Basic dynamic load rating
$C_0$	56,000 N	Basic static load rating
	0.5 kg	{重量}

### 安装尺寸

$L_1$	52.8 mm	Mounting dimension
$J_B$	30 mm	Mounting dimension
$J_L$	28 mm	Mounting dimension
$H_1$	0.2 mm	
$L_4$	63 mm	minimum support length
$L_W$	14 mm	
$H_4$	21 mm	
$T_5$	10.2 mm	
$G_1$	M6	fixing screws top (DIN ISO 4762-12.9)
$G_1 M_A$	17 Nm	Tightening torque fixing screws
$K_3$	M4	fixing screws below (DIN ISO 4762-12.9)
$K_3 M_{Amax}$	5 Nm	Tightening torque fixing screws
$D_2$	4.9 mm	
	6 mm	

### Related products

VUS26086-A	Adjustment gib
UG9741, UGN9741-A,	suitable Guide rail
UZ9741, UZN9741-A,	
UFK4710, UFB6412	

